

## SAFETY DATA SHEET

Revision Date 17-May-2020 Version 4

## 1. IDENTIFICATION

Product identifier

Product Name VERSACHEM PLASTIC TANK & RADIATOR REPAIR KIT (RESIN)

Other means of identification

Product Code 90214

Recommended use of the chemical and restrictions on use

Recommended Use Epoxy resin

Uses advised against No information available

Details of the supplier of the safety data sheet

**Manufacturer Address** 

ITW Permatex 6875 Parkland Blvd. Solon, Ohio 44139 USA

Telephone: 1-87-Permatex

(866) 732-9502

24-hour emergency phone number

Chem-Tel: 800-255-3924 International Emergency: 00+1+ 813-248-0585

Contract Number: MIS0003453

E-mail address: mail@permatex.com

May Also Be Distributed by:

ITW Permatex Canada 101-2360 Bristol Circle

Oakville, ON Canada L6H 6M5 Telephone: (800) 924-6994

## 2. HAZARDS IDENTIFICATION

#### Classification

#### **OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2A
Skin sensitization	Category 1
Carcinogenicity	Category 2

#### Label elements

## **Emergency Overview**

## Signal word Warning

Causes skin irritation
Causes serious eye irritation
May cause an allergic skin reaction
Suspected of causing cancer

REPAIR KIT (RESIN)

Revision Date 17-May-2020



Appearance Black Physical state Viscous liquid Odor Mild

#### **Precautionary Statements - Prevention**

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Use personal protective equipment as required

Wash face, hands and any exposed skin thoroughly after handling

Avoid breathing dust/fume/gas/mist/vapors/spray

Contaminated work clothing should not be allowed out of the workplace

Wear protective gloves/protective clothing/eye protection/face protection

#### **Precautionary Statements - Response**

IF exposed or concerned: Get medical advice/attention

Specific treatment (see .? on this label)

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

If eye irritation persists: Get medical advice/attention IF ON SKIN: Wash with plenty of soap and water Take off contaminated clothing and wash before reuse If skin irritation or rash occurs: Get medical advice/attention

## **Precautionary Statements - Storage**

Store in a well-ventilated place Keep container tightly closed Store locked up

#### **Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

#### Hazards not otherwise classified (HNOC)

Not applicable

#### Other Information

Not applicable.

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%
BIS[4-(2,3-EPOXYPROPOXY)PHENY	1675-54-3	60 - 100
L]PROPANE		
CARBON BLACK	1333-86-4	0.1 - 1
ALKYL GLYCIDYL ETHER	68609-97-2	0.1 - 1

## 4. FIRST AID MEASURES

## **Description of first aid measures**

**General advice** Get medical advice/attention if you feel unwell.

90214 - VERSACHEM PLASTIC TANK & RADIATOR REPAIR KIT (RESIN)

` '

Eye contact IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. If eye irritation persists: Get medical

Revision Date 17-May-2020

advice/attention.

Skin contact IF ON SKIN:. Wash with soap and water. If skin irritation or rash occurs: Get medical

advice/attention. Wash contaminated clothing before reuse.

Inhalation IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for

breathing. If symptoms persist, call a physician.

Ingestion IF SWALLOWED:. Do NOT induce vomiting. Never give anything by mouth to an

unconscious person. Call a physician.

Self-protection of the first aider Ensure that medical personnel are aware of the material(s) involved and take precautions to

protect themselves.

Most important symptoms and effects, both acute and delayed

**Symptoms** See section 2 for more information.

Indication of any immediate medical attention and special treatment needed

## 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Carbon dioxide (CO2), Use dry chemical, Foam

Unsuitable extinguishing media

None

Specific hazards arising from the chemical

None in particular.

**Explosion data** 

Sensitivity to Mechanical Impact None. Sensitivity to Static Discharge None.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

## 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

**Personal precautions** Ensure adequate ventilation, especially in confined areas. Avoid contact with eyes and skin.

Use personal protective equipment as required.

Environmental precautions

**Environmental precautions** See section 12 for additional ecological information.

Methods and material for containment and cleaning up

**Methods for containment** Prevent further leakage or spillage if safe to do so.

Methods for cleaning up

Use personal protective equipment as required. Dam up. Cover liquid spill with sand, earth

or other non-combustible absorbent material. Take up mechanically, placing in appropriate

Revision Date 17-May-2020

containers for disposal. Clean contaminated surface thoroughly.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

## 7. HANDLING AND STORAGE

Precautions for safe handling

Handle in accordance with good industrial hygiene and safety practice. Avoid breathing Advice on safe handling

> vapors or mists. Avoid contact with skin, eyes or clothing. Wash thoroughly after handling. Wash contaminated clothing before reuse. Use personal protective equipment as required.

Conditions for safe storage, including any incompatibilities

**Storage Conditions** Keep container tightly closed in a dry and well-ventilated place.

Strong oxidizing agents, Bases, Acids, Amines Incompatible materials

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Control parameters

**Exposure Guidelines** 

	Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Г	CARBON BLACK	TWA: 3 mg/m <sup>3</sup> inhalable particulate	TWA: 3.5 mg/m <sup>3</sup>	IDLH: 1750 mg/m <sup>3</sup>
	1333-86-4	matter	(vacated) TWA: 3.5 mg/m <sup>3</sup>	TWA: 3.5 mg/m <sup>3</sup>
				TWA: 0.1 mg/m³ Carbon black in
				presence of Polycyclic aromatic
				hydrocarbons PAH

NIOSH IDLH Immediately Dangerous to Life or Health

Other Information Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962

(11th Cir., 1992).

**Appropriate engineering controls** 

**Engineering Controls** Showers

> **Eyewash stations** Ventilation systems

Individual protection measures, such as personal protective equipment

Wear safety glasses with side shields (or goggles). Eye/face protection

Skin and body protection Wear protective natural rubber, nitrile rubber, Neoprene™ or PVC gloves.

Use NIOSH-approved air-purifying respirator with organic vapor cartridge or canister, as Respiratory protection

appropriate.

**General Hygiene Considerations** Handle in accordance with good industrial hygiene and safety practice. Regular cleaning of

equipment, work area and clothing is recommended.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Viscous liquid Physical state

Black **Appearance** Odor Mild

Odor threshold No information available

# 90214 - VERSACHEM PLASTIC TANK & RADIATOR REPAIR KIT (RESIN)

· ,

Air = 1

Revision Date 17-May-2020

<u>Property</u> <u>Values</u> <u>Remarks • Method</u>

pH No information available

Melting point / freezing point

Boiling point / boiling range
Flash point > 95 °C / > 302 °F

Evaporation rate
Flammability (solid, gas)

No information available
No information available
No information available

Flammability (solid, gas)
Flammability Limit in Air

Upper flammability limit:No information availableLower flammability limit:No information available

Vapor pressure 0.03 mmHg

Vapor density >1
Relative density 1.16
Water solubility Negligible

Solubility(ies) No information available Partition coefficient No information available **Autoignition temperature** No information available **Decomposition temperature** No information available Kinematic viscosity No information available Dynamic viscosity No information available **Explosive properties** No information available **Oxidizing properties** No information available

Other Information Softening point

Softening point
Molecular weight
Density
No information available
SADT (self-accelerating
No information available

decomposition temperature)

## 10. STABILITY AND REACTIVITY

#### Reactivity

No information available

#### **Chemical stability**

Stable under normal conditions

## Possibility of Hazardous Reactions

None under normal processing.

#### Conditions to avoid

Excessive heat.

#### Incompatible materials

Strong oxidizing agents, Bases, Acids, Amines

## **Hazardous Decomposition Products**

Carbon oxides Phenols

## 11. TOXICOLOGICAL INFORMATION

#### Information on likely routes of exposure

**Inhalation** May cause irritation of respiratory tract.

Eye contact Contact with eyes may cause irritation. May cause redness and tearing of the eyes.

**Skin contact** May cause skin irritation and/or dermatitis. May cause sensitization by skin contact.

REPAIR KIT (RESIN)

Revision Date 17-May-2020

Ingestion

Ingestion may cause irritation to mucous membranes.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
BIS[4-(2,3-EPOXYPROPOXY)PHE NYL]PROPANE 1675-54-3	= 11300 μL/kg (Rat)	= 20000 mg/kg(Rabbit)	-
CARBON BLACK 1333-86-4	> 15400 mg/kg (Rat)	-	> 4.6 mg/m³ (Rat) 4 h
ALKYL GLYCIDYL ETHER 68609-97-2	= 17100 mg/kg(Rat)	> 3987 mg/kg ( Rabbit )	-

#### Information on toxicological effects

**Symptoms** No information available.

## Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Sensitization Germ cell mutagenicity**No information available.
No information available.

**Carcinogenicity** The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
BIS[4-(2,3-EPOXYPROPOX Y)PHENYL]PROPANE 1675-54-3	-	Group 3	-	-
CARBON BLACK 1333-86-4	A3	Group 2B	-	X

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans

Not classifiable as a human carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

## The following values are calculated based on chapter 3.1 of the GHS document .

 ATEmix (oral)
 11427 mg/kg

 ATEmix (dermal)
 20285 mg/kg

## 12. ECOLOGICAL INFORMATION

#### **Ecotoxicity**

0.3 % of the mixture consists of component(s) of unknown hazards to the aquatic environment

#### Persistence and degradability

No information available.

## **Bioaccumulation**

No information available.

## **Mobility**

No information available.

#### Other adverse effects

No information available

## 13. DISPOSAL CONSIDERATIONS

## Waste treatment methods

## 90214 - VERSACHEM PLASTIC TANK & RADIATOR REPAIR KIT (RESIN)

ALPAIN NIT (NESIN)

Revision Date 17-May-2020

Disposal of wastes Disposal should be in accordance with applicable regional, national and local laws and

regulations.

**Contaminated packaging** Do not reuse container.

US EPA Waste Number Not applicable

## 14. TRANSPORT INFORMATION

DOT

Proper shipping name Not regulated

<u>IATA</u>

Proper shipping name Not regulated

**IMDG** 

Proper shipping name Not regulated

## 15. REGULATORY INFORMATION

## **International Inventories**

**TSCA** Complies Complies **DSL/NDSL EINECS/ELINCS** Not determined Complies **ENCS** Complies **IECSC KECL** Complies **PICCS** Complies **AICS** Complies

#### Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

**DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

**ENCS** - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

## US Federal Regulations

#### **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

## SARA 311/312 Hazard Categories

Acute health hazard Yes
Chronic Health Hazard No
Fire hazard No
Sudden release of pressure hazard No
Reactive Hazard No

#### **CWA (Clean Water Act)**

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

REPAIR KIT (RESIN)

Revision Date 17-May-2020

#### **CERCLA**

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material

## **US State Regulations**

**California Proposition 65** 

This product contains the following Proposition 65 chemicals

Chemical Name	California Proposition 65
1000 00 1	*Carcinogen (airborne, unbound particles of respirable size)

<sup>• \*</sup>The asterisked chemical(s) listed are not subject to Proposition 65 because they are not airborne in the finished product U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
CARBON BLACK	X	X	X
1333-86-4			

#### **U.S. EPA Label Information**

EPA Pesticide Registration Number Not applicable

#### **WHMIS Hazard Class**

D2B - Toxic materials

## 16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

NFPA Health hazards 2 Flammability 1 Instability 0 -

HMIS Health hazards 2 Flammability 1 Physical hazards 0 Personal protection B

NFPA (National Fire Protection Association) HMIS (Hazardous Material Information System)

Revision Date 17-May-2020

#### **Disclaimer**

Illinois Tool Works Inc. believes the information contained in this data sheet is accurate as of the date compiled. However, Illinois Tool Works Inc. makes no warranty, express or implied, as to the accuracy, reliability or completeness of the information. User is responsible for evaluating whether such information or this product is fit for a particular purpose and suitable for a particular use or application. The information in this data sheet may not be valid if this product is used in combination with other products or in processes for which it was not designed. Illinois Tool Works Inc. disclaims any liability for consequential or incidental damages of any kind, including lost profits, arising from the sale or use of this product. Ensure you have the most current version of this data sheet by contacting us or reviewing our web site.

**End of Safety Data Sheet**