



Copper Spray Gasket Sealant

Technical Data Sheet

Rev 02/22

PRODUCT DESCRIPTION: Copper Spray is a fast drying sealant that contains copper to help dissipate heat to prevent gasket blowout. Remains tacky to allow gasket repositioning. Fills surface imperfections.

WORKS BEST ON: Exhaust manifolds, carburetors, gaskets, cylinder head gaskets, turbo charges, flanged and other high performance applications.

PRODUCT FEATURES:

- Highly Flammable (Product is an aerosol, contents under pressure)
- Color: Metallic copper
- Full Bond: up to 24 hours.
- Temperature Resistance: -50°F to 525°F
- Chemical Solvent Resistance: shop fluids including gasoline.
- Storage: Store in a cool, dry environment in unopened container.

SURFACE PREPARATION: Provide adequate ventilation. Surfaces should be free of oil, dirt and grease. Mask off areas that should not be coated with Copper Spray.

REMOVAL METHODS:

Before Cure: Clean excess with isopropyl alcohol

After Cure: Cover the sealant with alcohol and allow to soften overnight.

HELPFUL HINTS: Shake can for one minute. For best results, aerosol can should be at room temperature before spraying. DO NOT Spray into engine compartment. Allow solvent to evaporate before assembly.

This product is not recommended for use in pure oxygen or oxygen rich systems and should not be used as a sealant for chlorine or other strong oxidizing materials.

After use, turn can upside-down and spray for a few seconds to unclog nozzle.

See MSDS for more complete information, safe handling instructions and first aid.

Consumer Commodity

Part Numbers: 88898



The technical data contained herein are intended as a reference only